

The home run

The series 2000 was the first line of speakers developed by System Fidelity and became an instant success. The enthusiast around Europe immediately realized the potential of this entry level series which was so more than that. For this price level very unusual features, as MDF cabinet, high quality tweeter with neodium magnet and equipped with cooling ribs instead of magnetic fluid which usually deteriorates the sound, and last but not least a price which was way down of the price, which we usually pay for this level of quality.

The first five-star reviews had just proved the statement of best sound for the money*.

***) Quote of the SF-2030 review in T3 magazine:**

"In most vital elements, the sound presented by SF-2030 was way above most of the speakers we have heard so far in this price level. Tonal balance and timbre were very good, and although the general sound spectrum leans on the bass area, the sound had plenty of character, and was generally warm and bodied. Despite the emphasized bass, it never loses control and there's never any boominess or distortions even when playing very loud. The dynamics is much more agile from any comparative speaker and the space dimensions of the sound are way above the average."

T3 verdict: ★★★★★

Milan Rupic, T3 Croatia, Sept. 2005

Four extraordinary 5.1 or 5.0 speaker sets are built with the speakers of series 2000. Regardless of the size or price level of the set, one can always be sure that one will get the maximum possible quality of sound, design and reliability.



SF-2105 / SF-2305



SF-2505



SF-2905



SF-2090



SF-2050



SF-2030



SF-2010



SF-125SW & SF-20CC

Tech. specifications:

	2010	2030	2050	2090	20CC	125SW
Configuration:	2-way	2-way	2-way	3-way	2-way	powered
Tweeter driver:	1"	1"	1"	1"	1"	-
Woofer driver:	4"	8"	2x4"	5x4"	2x4"	8"
Cabinet type:	closed MDF	bass-reflex	bass-reflex	bass-reflex	closed MDF	bass-reflex
Power handling:	80/120W	80/120W	120/180W	150/200W	100/150W	80/150W
Frequency response:	70Hz-20kHz	45Hz-20kHz	35Hz-20kHz	35Hz-20kHz	45Hz-20kHz	40Hz-150Hz
Sensitivity:	88dB	88dB	88dB	88dB	88dB	-
Impedance:	6 ohms	6 ohms	6 ohms	6 ohms	6 ohms	-
Crossover frequency:	3kHz	3kHz	2,5kHz	1/2,5kHz	2,5kHz	adjustable
Weight:	2,7kg	2,7kg	8 kg	11 kg	4,8 kg	8,8 kg
Dimensions (cm):	24x14x17,2	24x14x17,2	84x17,5x20	100x14x28	14x38,3x17,3	34x25x40

Available finish: cherry and black